

## LRD 2679/RED

WORK LIGHT LRD 2679/RED

### TECHNICAL DATA

Light group	Light category	LED light
HOR 111	working light	yes
LED quantity	Dispersed light	Wavelength of light
15	yes	628 nm
Side	Connection method	Supply voltage
universal	screw-on	12/24 V
Power rating	Cable	Operating temperature range
3,6 W	2x0,75 mm <sup>2</sup> ; cable length 1,5 m	from -30°C to +50°C
Light colour	Luminous flux	Ingress protection rating
red	100 lm	IP 68

### DESCRIPTION

**LRD 2679/RED work lamp - red light for special tasks.** The LRD 2679/RED lamp is a compact and efficient source of **diffused red light**, designed for operation in demanding conditions. With a power output of **3,6 W** and a **luminous flux of 100 lm**, it provides comfortable illumination of the work area without dazzling the operator or others nearby. Its **universal operating voltage (12/24 V)** and flexible mounting options allow for easy installation on various vehicles and machines. The durable housing and **IP 68 protection rating** ensure reliable performance even in extreme environments – mud, dust, rain, or snow pose no threat. The lamp meets **R10 (EMC)** standards, meaning it does not interfere with the vehicle's electronic systems. It can operate within a wide temperature range, making it a perfect all-season solution. The LRD 2679/RED lamp is ideal for service and road vehicles, where the red light effectively marks the working zone, enhancing safety in road traffic and during nighttime operations.

