LZD 2789/W2

FRONT MULTIFUNCTION LIGHT CLEOFRONT, SIDE MOUNT VERSION LZD 2789/W2

TECHNICAL DATA

Light group	Light category	LED light
HOR 115F	multifunction front	yes
LED quantity	**Front position light**	**Front direction indicator**
32	yes	yes
Side	**Supply voltage**	**Cable**
universal	12/24 V	3×0,5 mm2; cable length 1 m
Operating temperature range	**Ingress protection rating**	
from -30°C to +50°C	IP68	

DESCRIPTION

Attractive and modern design, compact sizes, high-quality materials and implemented energy-efficient LED technology, which ensures very good lighting parameters at very low power consumption, are the special hallmarks of multifunction lamp **CLEOfront LZD 2789/W2**. The lamp is fully hermetic (ingress protection rating IP 68), and the operating temperature range is from -30 degrees C to + 50 degrees C. Only branded diodes are used for production, and their number is 32 pcs. The operation of the lamp is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the EMC certificate. **LZD 2789/W2 of side mount version** is universal in assembly, it can be installed both on the left and right side of the vehicle, vertically and horizontally. The lamp fulfills the following functions: front position light with **NEON effect** and front direction indicator. This model is dedicated to various types of vehicles such as agricultural and construction machinery, specialized vehicles, forklifts, quads, light electric and municipal vehicles. **Power consumption at 12 V operating voltage:** – front position light (1,6 W); – front direction indicator (4,1 W). **Power consumption at 24 V operating voltage:** – front position light (3,6 W); – front direction indicator (4,6 W).

HORPOL A. Horeczy Sp.k.
NIP: 554-039-40-86
ul. Lipowa 3, 86-005 Lipinki
Biale Blota, Poland
+48 52 320 35 93
horpol@horpol.pl