LZD 2789/R1

FRONT MULTIFUNCTION LIGHT CLEOFRONT WITH SIDE DIRECTION INDICATOR, TUBE MOUNT VERSION LZD 2789/R1

TECHNICAL DATA

Light group	Light category	LED light
HOR 115F	multifunction front	yes
LED quantity	**Front position light**	**Front direction indicator**
33	yes	yes
Side direction indicator	**Side**	**Supply voltage**
yes	universal	12/24 V
Cable	**Operating temperature range**	**Ingress protection rating**
3×0,5 mm2; cable length 1 m	from -30°C to +50°C	IP68

DESCRIPTION

Attractive and modern design, compact sizes, high-quality materials and implemented energy-efficient LED technology, which ensures very good lighting parameters at very low power consumption, are the special hallmarks of multifunction lamp **CLEOfront LZD 2789/R1 with side direction indicator**. The lamp is fully hermetic (ingress protection rating IP 68), and the operating temperature range is from -30 degrees C to + 50 degrees C. Only branded diodes are used for production, and their number is 33 pcs. The operation of the lamp is also guaranteed in a way that does not emit electromagnetic interference and is electromagnetic interference-resistant, which is confirmed by the EMC certificate. **LZD 2789/R1 of tube mount version ø20÷30 mm** is universal in assembly, it can be installed both on the left and right side of the vehicle, vertically and horizontally. The lamp fulfills the following functions: front position light with **NEON effect,** front and side direction indicators. This model is dedicated to various types of vehicles such as agricultural and construction machinery, specialized vehicles, forklifts, quads, light electric and municipal vehicles. **Power consumption at 12 V operating voltage:** – front position light (1,6 W); – front direction indicator (4,1 W); – side direction indicator (0,2 W). **Power consumption at 24 V operating voltage:** – front position light (3,6 W); – front direction indicator (4,6 W); – side direction indicator (0,4 W).